

Shine Bright, Even in Dusty Depths

Technical Data

		HiLight V7+		
Light coverage m ²		7000 (average 20 luxes) LED		
Lamps		SMD		
Mast	Å	Vertical manual		
Extra features	*	HardHat Canopy		

	1	
Performance Data		
Rated frequency	Hz	50
Rated voltage	VAC	230
Rated power (PRP)	kW	5
Engine		
Make/Model		Kohler / KDW702
Speed	rpm	1500
Rated net output (PRP)	kW	5.1 @ 1500rpm
Cooling Type		Ethylene glycol based anti freeze
Number of cylinders		2
Alternator		
Make		Mecc Alte
Rated output	kVA	5
Enclosure protection	IP	21
Energy Consumption		
Fuel tank capacity	1	70
Run time with 4 lamps on with fuel tank	hrs	86
Power output		
Auxiliary power	kW	10 AMPS only if lamps are OFF
Lights		
Туре		SMD type LED
Wattage	W	4 x 350
Average luminosity over coverage area	lux	20
Average coverage area	m²	7000
Impact Protection	IK	IK10
Ingress Protection	IP	IP69
Mast		
Туре		Manual vertical, 5 section
Rotation	degrees	355
Maximum height	m	7.5
Maximum speed wind	km/h	85
Enclosure and trailer		
Enclosure		Gull-wing HardHat' doors
Dimensions and weight		
Dimensions in transport Fix Towbar (L x W x H)	m	1.9 X 1.1 X 2.5
Weight (Dry / Wet)	kg	664/764
5 . ,	5	

Contact:

Ankan Ghosal | +91 9073948993 | ankan.ghosal@atlascopco.com

Atlas Copco

Atlas Copco (India) Private Limited

[Formerly known as Atlas Copco (India) Limited]

Reach us: cr.india@atlascopco.com Toll free number: 1800 120 110030

atlascopco.com/en-in

Key applications










Market Leading LED Solutions

- Surface Mount Device (SMD) LED with Micro-Lens
- Smaller and more lightweight
- Energy-efficient LEDs, ideal for power sensitive applications.
- Impact Protection Standard: IK10
- Ingress Protection Standard: IP69

4 x 350W

Average light Intensity over 7000 m² area



Features



















